

ورق های فومیزه و فشرده PVC

ورق های PVC محصولاتی با خواص مکانیکی بسیار بالا هستند که قادرند نیازهای اقتصادی و زیست محیطی گوناگون را برآورده سازند. از جمله کاربردهای این مصنوعات می توان به رویه های میز، دیوار های جداکننده، سازه های نمایشگاهی و دکوراتیو و قطعات هندسی اشاره کرد. استابیلایزرهای شرکت همپار برلوفر بر پایه های سرب، قلع و ترکیبات نوین کلسیم روی این امکان را بوجود می آورند تا ورق های فشرده و فومیزه PVC به صورت تک لایه و سه لایه با کیفیت بالا، یکنواخت و با بازده تولید بالا تولید گردد.

همچنین استفاده از این استابیلایزرها ویژگی هایی همچون مقاومت در برابر مواد شیمیایی، مقاومت در شرایط گوناگون آب و هوایی، دانسیته پایین، رنگ سفید و قابلیت اشتعال پذیری اندک در محصول نهایی را به همراه دارد.

Baeropan	Metal basis	Characteristics	Dosage (phr)
MC 282 PLS/F/3	Pb	High dynamic heat stability, Excellent whiteness, free foam & celuka sheets	4 – 4.5
MC 283 PLS/F	Pb	High dynamic heat stability, Excellent whiteness, boosts expansion process	4 – 4.5
MC 9076 PS/22	Ca / Zn	High performance, Good self-lubrication, very good early colour & dynamic heat stability	4 – 5

Baerolub	Physical form	Properties
PA-L	Powder	High Release PVC metal, surface gloss will be improved
L-TP	Powder	Inner friction and melt viscosity will be reduced
Ceasit SW	Powder	Inner friction and melt viscosity will be reduced, pigment and filler dispersion will be improved

